



SSB-2001B

2-channel diver transceiver



Ordering information

SSB-2001B, 2 channel, no voice menu

T.99.01796

Based on the extremely popular AquaCom® SSB-2010, the AquaCom® SSB-2001B-2 transceiver is a 5 watt, dual-channel single sideband underwater telephone. Unlike the AquaCom® SSB-2010, the AquaCom® SSB-2001B-2 has no voice menus and only 2 channels. The AquaCom® SSB-2001B-2 can be configured to operate with virtually any style full face mask (FFM) or mouth mask. With the addition of a CDK-6 Surface Accessory Kit, the AquaCom® SSB-2001-B2 is easily converted into a portable surface station.

Standard features

- Voice Operated Transmitter (VOX)
- Push-to-talk control (PTT)
- Squelch
- 2 channels
- Earphone volumes
- Removable transducer
- Heavy duty design.

Specifications

- Nominal range: 200-1000m
- Channels: 1 and 7
- Channel selection: Selector switch
- Output power: 5 Watts
- Microphone/speakers: Requires a separate ear/microphone assembly
- PTT
- Transmit control: PTT
- Maximum depth: 300 fsw / 91 msw
- Battery type: 8-AA alkaline or RB-11 NiMH battery pack
- Battery life: Alkaline: 7h, NiMH: 8h
- Dimensions (HxWxD): 8.125" (20,64 cm) x 4.5" (11,43 cm) x 2.25" (5,72 cm)
- Weight: 0.6 pound (226,8 grams)

V-B

All rights reserved. Reproduction in any form or by any means is not allowed, without prior permission in writing from IHC Hytech BV

IHC Hytech BV

Ramgatseweg 27, 4941 VN, Raamsdonksveer
The Netherlands

T +31 162 52 22 02
F +31 162 51 90 69

hytech@royalihc.com
www.royalihc.com
www.ihchytech.com

The technology innovator.